



RATOTM

www.rato-europe.com


3

EDITION
2017

RT80WB26

RT50HB35

RT80NB20



APPLICAZIONI - APPLICATIONS

Caratteristiche:

RT80WB26-3.8Q e RT80NB20-5.2Q
per uso edilizio
RT50HN35-3.8Q: per acqua di mare,
materiali abrasivi e debolmente acidi

Features:

RT80WB26-3.8Q e RT80NB20-5.2Q
for building use
RT50HN35-3.8Q: seawater
plastic abrasive material, faintly acid



ACQUE SPORCHE TRASH PUMP

ACQUA DI MARE SEAWATER

Modello - Model			RT80WB26-3,8Q	RT80NB20-5,2Q	RT50HB35-3,8Q
Motore	Engine		R210	R270	R210
Tipo	Type		4 tempi, raffreddamento ad aria / 4-stroke, Air-cooled		
Carburante	Fuel		Benzina / Gasoline	Benzina / Gasoline	Benzina / Gasoline
Cilindrata	Displacement	ml	212	270	212
Pompa	Pump Set				
Aspirazione	Suction port	∅	80 (3")	80 (3")	50 (2")
Mandata	Discharge port	∅	80 (3")	80 (3")	50 (2")
Capacità aspirazione	Suction head lift	m	7	7	7
Prevalenza massima	Total head lift	m	26	20	35
Portata massima	Discharge capacity	l / min	1100	1100	533
Dimensioni	Dimensions	LxWxH mm	552x432x450	688x528x582	500x395x446
Peso	Weight	Kg	35	64	26



www.rato-europe.com
E-mail: info@rato-europe.com



*A seguito dei costanti sforzi dedicati al miglioramento dei nostri prodotti, procedure e dati tecnici possono cambiare senza preavviso.
Due to constants efforts to improve our products, certain procedures and specifications are subject to change without notice.*